



Model	KV	No-load current	Max Amps	Propeller	Max Voltage	Current	Pull	Power	Efficiency	Load current	No.of Cells (Lipo)	Weight (motor only)**	Weight w/ hardware**	Shaft Diameter	Resistance	Length of Extended Shaft
		(A)	(A)		(V)	(A)	(g)	(W)	(g/w)	(A)		(g)	(g)	(mm)	(ohm)	(mm)
LC4260-4T	720	2.8/10V	75	0 9 4 5	11.1	15	800	166.5	4.8	64	3-5S	281	311	5	0.015	20
					12.6	17.5	1000	220.5	4.53							
					14.8	23	1300	340.4	3.81							
					16.8	27.5	1600	462	3.46							
					18.5	33	2000	610.5	3.27							
				1 3 4 0	11.1	30	1900	333	5.71							
					12.6	34	2300	428.4	5.36							
					14.8	44	3100	651.2	4.76							
					16.8	54	3800	907.2	4.18							
					18.5	63	4700	1165.5	4.03							
LC4260-5T	580	2/10V	56	1 5 4 0	11.1	17.5	1500	194.25	7.72	48	3-5S	281	311	5	0.022	20
					12.6	21	1900	264.6	7.18							
					14.8	28	2600	414.4	6.27							
					16.8	33	3250	554.4	5.86							
					18.5	39	3900	721.5	5.4							
				1 5 6 0	21	48	5000	1008	4.96							
					11.1	24	2000	266.4	7.5							
					12.6	30	2500	378	6.61							
					14.8	39	3400	577.2	5.89							
					16.8	47	4100	789.6	5.19							
LC4260-6T	480	1.6/10V	50	1 5 4 0	11.1	11	1000	122.1	8.19	43	3-6S	281	311	5	0.0285	20
					12.6	13	1400	163.8	8.54							
					14.8	17	1850	251.6	7.35							
					16.8	20.5	2400	344.4	6.96							
					18.5	23.5	2800	434.75	6.44							
					21	29	3600	609	5.91							
					22.2	32	4000	710.4	5.63							
				1 5 6 0	25.2	39	5000	982.8	5.08							
					11.1	15.5	1500	172.05	8.71							
					12.6	19	1800	239.4	7.51							
LC4260-7T	420	1.3/10V	45	1 5 6 0	14.8	17	2000	251.6	7.94	38.5	4-6S	281	311	5	0.0415	20
					16.8	20.5	2400	344.4	6.96							
					18.5	24	2800	444	6.3							
					21	29	3600	609	5.91							
					22.2	32	4000	710.4	5.63							
					25.2	40	5100	1008	5.05							
				1 6 8 0	14.8	25	2600	370	7.02							
					16.8	30	3200	504	6.34							
					18.5	35	3700	647.5	5.71							
					21	42	4600	882	5.21							
LC4260-8T	370	1.1/10V	42	1 5 6 0	22.2	55	6100	1221	4.99	36	4-6S	281	311	5	0.0545	20
					14.8	12	1600	177.6	9							
					16.8	14.5	2000	243.6	8.21							
					18.5	16.5	2300	305.25	7.53							
					21	20.5	2800	430.5	6.5							
				1 6 8 0	22.2	22.5	3200	499.5	6.4							
					25.2	27.5	4100	693	5.91							
					14.8	17	2000	251.6	7.94							
					16.8	20.5	2500	344.4	7.25							
					18.5	24.5	3000	453.25	6.61							
1 6 8 0	21	30	3700	630	5.87											
	22.2	32	4100	710.4	5.77											
	25.2	39	5100	982.8	5.18											

LC4260-9T	330	0.9/10V	38	1 3 4 0	25.2	15.5	2400	390.6	6.14	32.5	6-12S	281	311	5	0.0665	20
					29.4	20	3700	588	6.29							
					33.6	24.5	4300	823.2	5.22							
					37.8	30	5400	1134	4.76							
					42	36.5	6300	1533	4.1							
LC4260-10T	300	0.8/10V	35	1 3 4 0	45	41.5	7000	1867.5	3.74	30	6-12S	281	311	5	0.0889	20
					25.2	12	2000	302.4	6.61							
					29.4	14.5	2600	426.3	6.09							
					33.6	18.5	3500	621.6	5.63							
					37.8	22	4300	831.6	5.17							
					42	26	5300	1092	4.85							
					45	30	6000	1350	4.44							
**All motors have been weighed in-shop by Altitude Hobbies. These weight figures are accurate and not underrated manufacturer estimates.																
Chart developed in collaboration with Leopard Hobby and not to be redistributed without permission. © Altitude Hobbies 2019																